

DC320V、DC720V

Quick Installation, simple maintenance and low maintenance cost

DC powered driven

Green and Environmental Protection.

Full digital control, easy to operate



Model		K-200E	K-300E
Unit installation mode		The condenser and compressor are integrated.	
Cooling capacity		2150W (0℃)	3150W (0℃)
		1250W (-18℃)	1750W (-18℃)
Volume of container (m3)		6 (-18℃)	12 (-18℃)
		10 (0℃)	16 (0℃)
Low Voltage		DC12/24V	DC12/24V
Condenser		Parallel flow	Parallel flow
Evaporator		copper pipe & Aluminum Foil fin	copper pipe & Aluminum Foil fin
			Foil fin
High Voltage		DC320V	DC320V
Compressor		GEV38	GEV38
Refrigerant		R404a	R404a
		1.0~1.1Kg	1.3~1.4Kg
Dimension (mm)	Evaporator	610×550×175	850×550×175
	Condenser	1360×530×365	1360×530×365
Standby Function		AC220V 50HZ (Option)	

Features of K-300E All Electric Truck Refrigeration Units

- ★ DC320V、DC720V
- ★ Quick Installation, simple maintenance and low maintenance cost
- ★ DC powered driven
- ★ Green and Environmental Protection.
- ★ Full digital control, easy to operate

