

DC320V、DC720V

Quick Installation, simple maintenance and low maintenance cost

DC powered driven

Green and Environmental Protection.

Full digital control, easy to operate

Model		K-400E	K-500E
Unit installation mode		Evaporator、 condenser and compressor are integrated.	
Cooling capacity		4650W (0℃)	5550W (0℃)
		2500 W (-18℃)	3100 W (-18℃)
Volume of container (m3)		18 (-18℃)	22 (-18℃)
		23 (0℃)	26 (0℃)
Low Voltage		DC12/24V	DC12/24V
Condenser		Parallel flow	Parallel flow
Evaporator		copper pipe & Aluminum Foil fin	copper pipe & Aluminum Foil fin
		Foil fin	Foil fin
High Voltage		DC320V/DC540V	DC320V/DC540V
Compressor		GEV38	GEV38
Refrigerant		R404a	R404a
		1.9~2.0Kg	2.1~2.2Kg
Dimension (mm)	Evaporator		
	Condenser	1600×809×605	1600×809×605
Standby Function		(Option, Only For DC320V Unit)	

Features of K-300E All Electric Truck Refrigeration Units

- ★ DC320V、DC720V
- ★ Quick Installation, simple maintenance and low maintenance cost
- ★ DC powered driven
- ★ Green and Environmental Protection.
- ★ Full digital control, easy to operate

Application

