

K-660 Direct Engine Driven

K-660Truck chiller refrigeration truck units have front mounting and rooftop mounting, driven by vehicle engine and apply for medium or big trucks with 20~25m³ Truck body box or 5.2 meter length truck body to keep temperature range from -18°C to +25°C.

The Truck reefer units with chiller and freezing function for transporting fresh fruits, milk ,ice cream ,vegetables, meat, dairy products and seafood...

K-660Truck Refrigeration System Optional Functions

- AC220V/1Ph/50Hz or AC380V/3Ph/50Hz
- Optional electric standby system AC 220V/380V

K-660 Transport refrigeration units Features

- Multi-function controller with microprocessor control system
- The units with CPR valve will better protect compressors, especially in extremely hot or cold place.
- Adopt Eco-friendly refrigerant: R404a
- The Hot gas defrosting system with Auto and manual is available for your choices
- Rooftop mounted unit and slim evaporator design
- Strong refrigeration,cooling fast with short time
- High-strength plastic enclosure,elegant appearance
- Quick installation,simple maintenance an low maintenance cost
- Famous brand compressor:such as Valeo compressor TM16,TM21,QP16,QP21 compressor , Sanden compressor, highly compressor etc.
- International Certification : ISO9001,EU/CE ATP ,etc

Model		K-660
Temperature Range(In Container)		-20℃ ~ +30℃ / 0°F ~ +86°F
Cooling Capacity	0℃/+32°F	5050W / 6745Kcal/h / 18000BTU
	-20℃/ 0°F	2890 / 3489Kcal/h / 9980BTU
Compressor	Model	QP16/TM16
	Displacement	163cc/r
	Weight	8.9kg
Condenser	Coil	Copper Tube & Aluminum Fin
	Fan	Two Fans (DC12V/24V)
	Dimensions	1367*514*365 mm
	Weight	33 kg
Evaporator	Coil	Copper Tube & Aluminum Fin
	Fan	Three Italy Spal Fans(DC12V/24V)
	Air flow	4200m ³ /h
	Dimensions	1475×649×230 mm
	Weight	34 kg
Voltage		DC12V / DC24V
Refrigerant		R404a/1.7-1.8kg
Defrosting		Hot gas defrosting(Auto./Manual)
Application		20~25m ³

Application

